

Guidelines for Maintenance and Cleaning

1. All Panel coverings regardless of finish are subject to soiling and wear. A regular maintenance program initiated at the earliest possible time after installation will go a long way toward preventing soil and dirt build up or staining of the panel. Extra cleaning and preventive maintenance is necessary in areas adjacent to air conditioning or air-return vents.
2. PERFORATED VINYL is a delicate material and should be handled very gently. The surface may be marked or broken with abrasive material or chemicals.
3. Where fabric faced panels are concerned, the fabric manufacturers' instructions should be followed where they do not conflict with information below.
4. Cleaning agents used on the surface should not contain alcohol, strong alkalis or solvents which will react to the vinyl or adhesives used in the panels. Warm water with a mild soap should be used for cleaning.
5. Care should be taken in using cleaning agents and pesticide control products as the fumes may contain agents which will react to adhesives bonding to the surface material to the core, causing a loosening of the bond and result in sagging surface material.
6. Temperature should be maintained between 50 degrees Fahrenheit and 85 degrees Fahrenheit. Humidity should be maintained between 20 and 50 percent for maximum life of panels.
7. The panel should never be placed in water or allowed to become wet inside the core.
8. Test any cleaning agents on a piece at the rear of a panel before using in the face.
9. Grease or oil should be wiped off immediately upon contact. Remove excess grease or oil by blotting. Use hot water and mild soap to remove any remaining material.
10. DO NOT handle the panels any more than necessary. Avoid bending or flexing panels as it may break the bond between surface material and the core.
11. Avoid contact with any sharp edges on material that may cause a puncture on the surface.
12. Avoid excess heat or moisture as they may affect finish and adhesives.