

110 SERIES TACKBOARDS

PART 1 GENERAL (SCOPE)

1.01 DESCRIPTION OF WORK

FURNISHING AND INSTALLING THE FOLLOWING ITEMS: Fixed tackboards

1.02 RELATED WORK

- A. Division 04000 masonry block wall.
- B. Division 06100 blocking for all units at locations shown on shop drawings for attachment devices.
- C. Division 09000 gypsum wall board.

1.03 REFERENCES

- A. ASTM C540 Gloss for ceramic materials.
- B. ASTM C614 for alkali resistance.
- C. ASTM D2244 evaluation of color differences.
- D. ASTM B221-83 for aluminum extrusions.
- E. ASTM C208-72 for cellulosic fiberboard.
- F. ANSI A208.1-79 for particleboard.
- G. ANSI H35.1-82 for aluminum temper and alloy.
- H. ANSI A424-80 for steel for porcelain enameling.
- I. FS LLL-B-810 for tempered hardboard.
- J. ANSI IES-RP-3 for school lighting (by others).
- K. PEI -104 minimums for porcelain enameling.
- L. BYK-Gardner Surface Coating.

1.04 SUBMITTALS

- A. Samples and colors for each:
 - 1. Cork materials
 - 2. Vinyl materials
 - 3. Aluminum trim types and profiles.
- B. Anchoring devices
- C. Accessories
- D. Warranty and certificate of authenticity from manufacturer.
- E. Product use and maintenance instructions.
- F. Drawings shall indicate location and actual material lengths of each unit. Room elevations shall indicate joint locations and include dimension from floor and adjacent sidewalls, cross-sections for trim, backing ,face and core materials, fastener spacing and types of units provided.

1.06 DELIVERY AND STORAGE

- A. All pre-framed units shall be stored vertically and with packing materials between each to prevent damage.
 - B. Cover all units to prevent damage and dirt accumulation.
- A. 1.07 PROJECT CONDITIONS
- A. Store materials in dry areas and above temperatures above 55 degrees F.
 - B. General contractor to maintain proper environment prior to, during, and after installation.
 - C. Adhesives are to be used with adequate ventilation.

1.08 WARRANTY

Manufacturer shall be one who offers a national advertised written guarantee specifically covering the porcelain finish- that the original writing and erasing surface will retain its writing and erasing qualities and maintain its gloss variance, gloss reflectance, and color consistency for the life of the building.

110 SERIES TACKBOARDS

1.09 MAINTENANCE

Submit manufacturers' standard instructions for cleaning and stain removal.

PART 2 GENERAL (MATERIALS)

2.01 MANUFACTURERS

- A. Acceptable manufacturers:
 - 1. Polyvision (110 Series) as provided by WIUSA.com, P.O. Box 567949, Dallas, TX 75356, 800-527-9014, FAX 214-631-4654, web: www.wiusa.com, email: sales@wiusa.com.
 - 2. Products as manufactured by other manufacturers must comply with all requirements of the specifications.
- B. Substitutions shall be made 21 days in advance of the bid date. Manufacturers' must submit all data required in its entirety for review by the architect. Samples of the facing sheet showing progressive enamel coatings along with metering devices capable of measuring coating thickness, ground coat thickness, manufacturers' certificate of compliance of all items. Prior to consideration, lamination and fabrication sections must be submitted to the architect for testing and also inspection of methods and quality (samples will be retained).

2.03 MATERIALS FOR TACKABLE SURFACES**

- A. Core materials* (choose from):
 - 1. 1/4" hardboard
 - 2. 3/8" industrial fiberboard
 - 3. 7/16" industrial fiberboard
 - 4. 1/2" industrial fiberboard
- C. Natural cork* (choose from):
 - 1. 1/4" thickness
 - 2. 1/8" thickness
 - 3. 1/16" thickness
- D. Linoleum grade cork with burlap backing* (choose from):
 - 1. 1/4" thickness
 - 2. 1/8" Thickness
- E. Vinyl covering (choose from):
 - 1. 15 oz. per L.Y.-Nacoweave I or Nacoweave IA
 - 2. 20 oz. per L.Y.-Nacoweave II, Nacolinen, Nacotwill, Nacostar
 - 3. 34 oz. per L.Y.-Self-sealing foam vinyl-Naco Vinyl Plus
- F. Fabric covering
 - 1. 2- ply 100% polyester fabric with plain weave pattern.
 - 2. 16.0 oz. per L.Y.
- G. Lamination
 - 1. Factory machine type.
 - 2. Specially formulated adhesives.
- H. Attachment devices
 - 1. Adjustable slotted wall brackets (zinc plated).
 - 2. Attachment screws (for bracket attachment to boards).

*All thickness' are nominal.

** Total laminated thickness of materials to equal 1/2".

110 SERIES TACKBOARDS

PART 3 GENERAL

3.01 INSTALLATION

- A. Provide factory trained installers.
- B. Apply manufacturer's adhesive behind each board using egg sized gobs 16" on center.
- C. Mounting heights from the floor for each room shall be:
 - 1. Kindergarten 24"
 - 2. First - third grades 26"
 - 3. Fourth - sixth grades 30"
 - 4. Seventh - ninth grades 34"
 - 5. Tenth and up grades 37"
- D. Provide covering for H-moldings to match vinyl covered boards.
- E. Clean boards using manufacturers' recommended procedures and install cleaning labels for each room.
- F. Locate accessories on each board as specified.
- G. Provide mitered and wrapped hairline joints for all trims.
- H. Provide fasteners at perimeter trims 16" - 24" and 12" - 16" on trays.

3.02 PROTECTION

General Contractor shall cover and protect all boards after installation and cleaning.

3.03 CLOSEOUT DOCUMENTS

Provide all maintenance and warranty, cleaning and use documents to General Contractor.