

PART 1 - GENERAL

1.01 DESCRIPTION OF WORK

- A. This section includes Premiere Wall-Mounted Trophy and Display Cases
- B. This section includes Imperial Series Wall-Mounted Trophy and Display Cases

1.02 REFERENCED STANDARDS

- A. ASTM-E 84
- B. ASTM B221

1.03 SUBMITTALS

- A. Shop Drawings: Provide shop drawings for each type of wall-mounted display or trophy case required.
- B. Product Data: Provide technical data for materials specified. Include Material Safety Data Sheets, when applicable.
- C. Samples:
 - 1. Manufacturer's color charts
 - 2. Composition samples of material and trim to illustrate finish, color and texture.

1.04 OPERATION & MAINTENANCE

- A. Include data on regular cleaning, stain removal, and precautions.

1.05 REGULATORY REQUIREMENTS

- A. Conform to applicable code for flame/smoke rating in tackboards in accordance with ASTM-E 84.

1.06 QUALITY ASSURANCE

- A. Provide all items in this section as provided by:
 - WIUSA.com
 - PO Box 567949
 - Dallas, TX 75356
 - Phone: 800-527-9014; Fax: 214-631-4654
 - www.wiusa.com
 - sales@wiusa.com

1.07 FIELD CONDITIONS

- A. Field measure prior to preparation of shop drawings and fabrication to ensure proper fit.

1.08 WARRANTY

- A. Submit a standard warranty, stating when installed in accordance with manufacturer's instructions and recommendations, Claridge trophy and display cases are guaranteed for one year against defects in materials and workmanship. Guarantee does not cover normal wear and tear, improper handling, any misuse, or any defects caused by vandalism or subsequent abuse. Guarantee covers replacement of defective material but does not include cost of removal or reinstallation.

PART 2 - PRODUCTS

2.01 MANUFACTURERS

- A. Premiere and Imperial Series Wall-Mounted Display and Trophy Cases as manufactured by: Claridge Products and Equipment, Inc., as provided by WIUSA.com, PO Box 567949, Dallas, TX 75356, 800-527-9014, FAX: 214-631-4654, www.wiusa.com, sales@wiusa.com.

2.02 MATERIALS

- A. Imperial Series Wall Mounted Trophy and Display Cases
 - 1. Architect to select from Claridge Cork, Fabricork, Hook-Fab, Designer Fabric and Tan Nucork tackable back panel or Walnut or Oak grained low-pressure laminate finish back panel.
 - 2. Standard sizes: 3' x 4' x 7"; 4' x 5' x 7"; 4' x 6' x 7"; 4' x 5' x 10-3/4"; 4' x 6' x 10-3/4"; inside depth of 7" cases is 5-1/8"; inside depth of 10-3/4" cases is 8-7/8"
 - 3. Housing: Perimeter trim is 1-1/4" x 3-1/4" extruded aluminum with satin anodize finish.
 - 4. Header Panel: Architect to specify if 6" translucent Plexiglas header required.
- B. Glass Doors: Glass doors are 3/16" tempered, unless otherwise specified.
 - 1. Sliding door cases have ground-in finger pulls, doors slide on glides, and are fitted with flat key tumbler locks.
 - 2. Premiere cases have three 6, 8, 10 or 12-inch wide (as specified) adjustable glass shelves; 7-inch deep Imperials have 4-inch shelves; 10-3/4-inch Imperials have 8-inch shelves.
 - 3. Necessary brackets and shelf standards provided.
- C. Metal Trim and Accessories: Provide aluminum extrusions as manufactured by Claridge Products and Equipment, Inc. Trim shall be heavy gauge extruded aluminum and shall meet or exceed ASTM B221 Alloy Standards. Finish to be etched and anodized satin finish.
- D. Colors: As selected from manufacturer's standard colors. Over 50 standard tackboard colors to choose from. Color charts furnished on request.
- E. Options: Color anodize or powder coat finish on trim; fluorescent lights

2.03 FABRICATION

- A. Shop assembly: Provide factory assembled cases to requirements indicated on shop drawings.
- B. Units shall be of dimensions shown in details and in accordance with manufacturer's shop drawings, as approved by architect.

PART 3 - EXECUTION

3.01 PROJECT CONDITIONS

- A. Verify before installation that interior moisture and temperature approximate normal occupied conditions.
- B. Verify that floor and wall surfaces are prepared and ready to receive cases.

3.02 INSTALLATION

- A. Deliver cases set up, made in one piece.
- B. Follow manufacturer's instructions for storage and handling of units before installation.
- C. Install level and plumb, in accordance with manufacturer's recommendations.

3.03 ADJUST AND CLEAN

- A. Verify that all accessories are installed as required for each unit.
- B. At completion of work, clean glass surfaces, back panels and trim in accordance with manufacturer's recommendations, leaving all materials ready for use.